



# **RP 4150** THERMAL PRINTER

Expand your vision











Versatile Roll Capacity Up To 112 mm (4 Inch Width) - Prints wider & bigger



High Capacity Paper Width Roll Up To 102 mm - Paper roll need not be changed often



Standard Dual Interface Of Parallel & USB -Multiple connectivity option



Built-In Auto Cutter -Cuts the bills at the end of the print



Built-In Power Adapter -Sleek design to improve aesthetics





#### The RP 4150 Advantage

With the ever increasing customer demand for better clarity of bills, printing wider bills has become the need of the hour. Certain segments of retailers today prefer to expand the size of the bill from 3" to 4" (40 col to 60 col). RP 4150 is specifically designed for customers who want wider bills with superior quality. With a print speed of 150 mm / sec and an inbuilt auto cutter, it enables smooth flow of bills. With a capacity to hold a paper roll diameter of 102 mm, it reduces the need to change the paper roll frequently and therefore ensures hassle free operations. It also comes with a standard built-in USB and parallel interface giving the user multiple connectivity options.

All this comes from a brand that has been the epitome of trust - TVS Electronics, a company which has understood the Indian retailer like no other.

#### **Specifications**

Printing Method : Direct thermal
Printing Speed : 150 mm / sec

Dot Density : 203 dpi

Dot Pitch : 8 x 8 dots / mm

Character Per Line: Font A - 69 columns; Font B - 92

columns; Font C - 104 columns

[at 112 mm paper width]

Character Set : Alphanumeric, International, PC437

PC850 / 852 / 857 / 858 / 860 / 863 /

864 / 865 / 866

Barcode Fonts : UPC-A/E, JAN(EAN) 13/8 columns,

ITF, CODE 39, CODE 128, CODABAR

(NW-7), CODE 93, PDF417, QR code

Paper Width : 112 mm

Paper Thickness : 0.065 - 0.15 mm

Paper Roll : Max. ~102 mm

Diameter

Printing Width : 104 mm / 832 dots

Interface : Parallel, USB

Optional : Serial

User Memory : 384 KB (capable of storing user-defined

characters and logos)

Buffer Size : 4 KB / 45 bytes in parallel;

16KB in USB

Emulation : ESC / POS

Driver : Windows 7, Vista, 2K, XP, Linux,

OPOS, VCOM

Cash Drawer : 1 port

Reliability : 100 km

(Print Head Life)

Physical:  $177 \times 213 \times 147$ 

Dimensions

(W x D x H) mm

Auto Cutter Life : 1 million cuts

Cutting Method : Full / partial cut

Supply Voltage : AC 100 ~ 240V, 50 ~ 60Hz;

DC 24V ± 7%

Operating : 5° to 45°C

Temperature

Storage : -20° to 60°C


Temperature

Operating Humidity: 10% to 90% RH

Storage Humidity : 10% to 90% RH

Certifications : FCC, CE

Features : Wall mountable, built-in AC adapter



#### TVS ELECTRONICS LIMITED:

South Phase 7A, Second Floor, Industrial Estate, Guindy, Chennai - 600 032. Call: 1800 200 5123 / 3030 9797 (prefix city STD code) Visit: www.tvs-e.in

## ORDERING INFORMATION

3006210017 RP 4150

#### **OPTIONAL ACCESSORIES**

2021110023 RP 4150 SERIAL CARD

### **DEALER STAMP**